

A G A T E X B TECHNICAL SHEET (according to the standard UNI EN ISO 14465)

ARTICLE:	VGT 1726 TP - FRESIA STRETCH
COMPOSITION:	90%PL 10%SP
WEIGHT G/M LIN.:	630 gr/mtl
REPEAT(WARP/WEFT):	NO
METERS PER ROLL:	40 MT
WIDHT CM:	140



MADE IN ITALY

www.vagatexitalia.it









- Abrasion Resistance - Martindale UNI EN ISO 12947-2 + EN 14465, appendice A	Color degradation after 3000 giri: 4 Color degradation after 6000 giri: 4 END POINT (rubs): > 30.000
Pilling resistance by the modified martindale method UNI EN ISO 12945-2	Degradation average photographic scale 1/5 : 4 At 2000 rubs: 4/5
Colour fastness to light UNI EN ISO 105-B02	Blue scale 1/8 result: 4/5
Colour fastness to rubbing UNI EN ISO 105-X12	Grey scale 1/5 dry: 4 wet: 3/4
Dimensional change after washing UNI EN ISO 6330	Narrowing (weft): <= +-3% Shortening (warp): <= +-3%
Dimensional change after dry cleaning UNI EN ISO 3175	Narrowing (weft): <= +-3% Shortening (warp): <= +-3%
Resistance to yarn Slippage at stitched seams UNI EN ISO 13937-3 (din 14465)	Weft mm < 6 warp mm < 6
Fire Resistance	- AVAILABLE ON REQUEST
Environmental benefits	 No use of AZO dyes, which may split off carcinogenic acrylic amines. No use of dyes containing heavy metals/complies with ETAD norm. No use of brominated flame retardants. Compiles with REACH regulation.
Sustainability	ECO PATH AVAILABLE ON REQUEST
Available teflon treatment	(on request)
Type of finish used	SPECIAL FINISH FOR STRETCH ITEMS
Tariff code	6001920000
Raw Material & Weaving	Made in Italy



MADE IN ITALY

www.vagatexitalia.it

