



ARTICLE:	VGT 2495 TF/ACC
COMPOSITION:	95%PL 5%EA
WEIGHT G/M LIN.:	840 gr/mtl
REPEAT(WARP/WEFT):	NO
METERS PER ROLL:	35 MT
WIDHT CM:	140



MADE IN ITALY

www.vagatexitalia.it









- Abrasion Resistance -	Color degradation after 3000 giri: 5
Martindale	Color degradation after 6000 giri: 5
UNI EN ISO 12947-2 + EN 14465, appendice A	END POINT (rubs): > 60.000
Pilling resistance by the modified	Degradation average photographic scale 1/5 : 5
martindale method UNI EN ISO 12945-2	At 2000 rubs: 5
Colour fastness to light UNI EN ISO 105-B02	Blue scale 1/8 result: 4/5
Colour fastness to rubbing UNI EN ISO 105-X12	Grey scale 1/5 dry: 4 wet: 3/4
Dimensional change after washing	Narrowing (weft): <= +-3% Shortening (warp): <= +-3%
UNI EN ISO 6330	
Dimensional change after dry cleaning	Narrowing (weft): <= +-3% Shortening (warp): <= +-3%
UNI EN ISO 3175	
Resistance to yarn Slippage at stitched	Weft mm < 6 warp mm < 6
seams UNI EN ISO 13937-3 (din 14465)	
	TREATED IN FOULARD:
Fire Resistance	- A: BS 5852 CIGARETTE
	 B: TB 117 CALIFORNIA C: OTHER TEST AVAILABLE ON REQUEST
	 No use of AZO dyes, which may split off carcinogenic acrylic amines.
	- No use of dyes containing heavy metals/complies with ETAD
Environmental benefits	norm.
	 No use of brominated flame retardants.
	 Compiles with REACH regulation.
Sustainability	ECO-PATH AVAIBLE
Available teflon treatment	(on request)
Type of finish used	EXCLUSIVE FINISH FOR STRETCH ITEM
Tariff code	6004100010
Raw Material & Weaving	Made in Italy



MADE IN ITALY

www.vagatexitalia.it

